

2105-57 industrial ethernet ring switch



Key features

- Fault-tolerant self-healing ring (SHR) with 30ms plus 5ms per hop Recovery time
- Pre-configured from factory for SHR operation
- 10/100 Base-T(X) (RJ45), 100 Base-FX (SC or ST optical fiber connectors, multi/single mode)
- Supports IEEE 802.3/802.3u/802.3z/802.1p
- Intelligent store and forward, non-blocking

Overview

The EOTec 2104 is a rugged, high performance Industrial Ethernet ring switch that is designed to fill the gap between unmanaged and managed Ethernet switches. It provides all the benefits of redundant ring topology operation, but at a significantly lower cost than managed switches. The 2104 features the simplicity of installation and operation of an unmanaged switch, while retaining many of the capabilities of a managed switch. It is pre-configured for ring topology and no setup or configuration is required. It doesn't require master switch selection or an IP address to operate in a redundant ring topology. Its ultra fast link loss recovery time ensures high reliability with minimal downtime.

Technical specification

Key features (continued)

- Real-time traffic prioritization
- 45mm wide, DIN rail mounted
- Universal redundant power supply available
- Low power consumption (8W)
- Power and switch status LED indicator
- Global ring status alarm LED indicator
- Expandable backplane
- Remote status monitoring using Modbus over Ethernet (UDP)
- Local and global relay alarm contacts
- Port status ACT and LINK LEDs combined into one LED per port
- Backplane port activity status LED indicator
- Two SC or ST 100base-FX (multi-mode and single mode) fiber optic ports
- Pre-configured for redundant self-healing ring operation
- Full/half duplex, MDI/MDIX auto crossover, auto negotiate, auto polarity
- Expandable up to 8 ports
- Long-haul transmit distances of 2, 15, 40 and 60km

Feature	Description
Fiber type	Multi-mode
Connector type	SC
Port configuration	4-Port (2 RJ45 & 2 Fiber)
Power requirements	15-40 Vdc via screw terminals
Maximum transmission distance	2km
Operating temperature range	-40 to +85°C
Approvals	Class 1, Division 2, Groups A, B, C, D - CE Marked
User manual	Shipped with product or available on request
Accessories	<ul style="list-style-type: none"> • Optional power supply modules: 2A06, 2A16 • Expansion modules for additional ports: 2E54, 2E56, 2E58, 2E60, 2E62, 2E52

United States of America

707 Jeffrey Way
Round Rock
Texas 78665-2408
USA

Tel: +1 512-434-2800

United Kingdom

Innovation House
Lancaster Road
Ferndown Industrial Estate
Wimborne
Dorset BH21 7SQ
UK

Tel: +44 (0) 1202 850 450

For more information

Web: cwic.curtisswright.com

Email: sales@nspi.curtisswright.com

About Curtiss-Wright

Curtiss-Wright Round Rock and Wimborne have worked with nuclear and industrial customers for over 60 years. We support customers across the world from facilities located in the US and UK. Our solutions are embedded in strategic national infrastructure and our people are active partners in customer programs that are focused on delivering advanced future nuclear and industrial capabilities.

Curtiss-Wright Corporation (NYSE: CW) is a global integrated business that provides highly engineered products, solutions and services mainly to Aerospace & Defense markets, as well as critical technologies in demanding commercial power, process and industrial markets. We leverage a workforce of approximately 8,600 highly skilled employees who develop, design and build what we believe are the best engineered solutions to the markets we serve. Building on the heritage of Glenn Curtiss and the Wright brothers, Curtiss-Wright has a long tradition of providing innovative solutions through trusted customer relationships.